

# Slim LED Downlight - 4"/6"

## Specification Sheet

# 230629-x



### APPLICATIONS FEATURES

- General Lighting
- Retail
- Commercial
- Residential
- Hospitals
- Office and more...
- IC Rated
- Airtight
- Dimmable
- Works with several dimmers, **CONTACT US** for dimmer list
- Suitable for wet locations
- Switch for colour change (Selectable)

### SPECIFICATIONS

Junction Box: 3.6" x 3.33" x 1.3"  
 Wire Length: 18"  
 Clip: 1.65"  
 Colour Temperature: White 3000K, 4000K, 5000K  
 Material: Aluminium, plastic  
 Weight 177g to 280g  
 Beam Angle: 100°  
 Power Factor: >0.9  
 Lifespan: >50,000 hours  
 LED Type: SMD2835  
 Remark: Direct replacement

Model	Power	Volts	CRI	Lumens	Efficiency	Body	Trim
DL04-044-11WH8S	11W	120V	>90	750	68	4.1" x .48"	4.97" x .1"
DL04-044-11BK8S	11W	120V	>90	750	68	4.1" x .48"	4.97" x .1"
DL06-045-14WH8S	14W	120V	>80	1000	71	6.3" x .48"	7.1" x .1"

### POWER ENVIRONMENT

Input Voltage: 120V

### WORKING ENVIRONMENT

Temperature: -20°C to 40°C

### BENEFITS

- 4" Downlight available in black or white
- 6" Downlight available in white
- Can be directly in contact with insulation materials
- Low voltage
- No potlight box required
- Even light output
- Thin profile
- Same depth as drywall

