

Linear Wall Washer

Specification Sheet

23401x



APPLICATIONS FEATURES

- Wall Washing
- Down lighting for decks
- Architectural lighting
- Stairways
- Displays
- Office and more
- IP65 Rated
- Stainless steel hardware
- Swivel base
- Waterproof silicone gasket connection
- 25°, 42°, 60°, 90° beam angle, 90° rotating angle

SPECIFICATIONS

Size: 500mm x 56mm x 53mm
 1000mm x 56mm x 53mm
 Colour: 3000K, 4000K, 5000K, 6000K, RGB and RGBW
 Material: Aluminium housing, glass, stainless steel
 Weight: 3.2lbs - 5.6lbs
 Lifespan: 50,000 hours
 Remark: Direct replacement
 Wattage: Available in 18 & 36 Watt



BENEFITS

- Easy to install
- Energy efficient
- IP65 Construction

POWER ENVIRONMENT

Input Voltage: 24AC

WORKING ENVIRONMENT

Indoor/Outdoor covered IP65



Part Number	Power	IP Rating	Colour	Sizes	Beam Angles
234016-500	24V	IP65	3000, 4000, 5000, Single Colour	500mm	15/25/45/60/90
234016-1000	24V	IP65	3000, 4000, 5000, Single Colour	1000mm	15/25/45/60/90
234017-500	24V	IP65	RGB	500mm	15/25/45/60/90
234017-1000	24V	IP65	RGB	1000mm	15/25/45/60/90
234018-500	24V	IP65	RGBW	500mm	15/25/45/60/90
234018-1000	24V	IP65	RGBW	1000mm	15/25/45/60/90

