851103-FL60-VDC





Powered by the standard 5050 standard SMD LED Chip, this flexible LED is great for general lighting applications. Available in a wide range of whites and multiple voltages.



Experience the brilliance of Zortech LED's ALO3 kit, featuring the FL60 (5050 SMD LED, 60 LED/m) strip and AL03 aluminum extrusion. Effortlessly combine LED illumination with the sleek ALO3 square recessed extrusion for a stunning lighting solution that adds both style and efficiency to any setting.

- ·Standard Semi-Clear (Frosted) Cover, other options available
- ·Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request
- ·Variety of lead and wire options, at additional cost

Colour Temperature (K)



Lens Options







Mounting Options









Product Details

Part Number	FL60, FL60 CC
Width	10mm wide, 5m spool
LED Count/m	60 LED/m (FL60, FL60 CC)
Cuttable Length	50mm (FL60, FL60 CC)
CRI	>80+ (FL60 CC) >90+ (FL60)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Lumens 1000 lms/m (FL60) 1200 lms/m (FL60 CC)

Flectrical

Electrical	
Input Voltage	12 VDC (Standard) 24 VDC (Standard, FL60 CC)
Power Consumption	14.4 W/m (FL60) 12 W/m (FL60 CC)
Wire	Barrel, Locking Tab, Small Locking Tab, Blunt Wire