





Experience the brilliance of Zortech LED's AL03 kit, featuring the FS180 (2216 SMD LED, 180 LED/m) strip and AL03 aluminum extrusion. Effortlessly combine high density LED illumination with the sleek AL03 square recessed extrusion for a stunning lighting solution that adds both style and efficiency to any setting.

•Standard Semi-Clear (Frosted) Cover, other options available •Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request

 $\cdot Variety$  of lead and wire options, at additional cost

Product Details	
Part Number	FS180
Width	10mm wide, 5m spool
LED Count/m	180 LEDs/m (FS180)
Cuttable Length	17mm (FS180 12 VDC) 35mm (FS180 24 VDC)
CRI	>90+ (FS180)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Powered by the standard 2216 super small SMD LED Chip, this flexible LED is great for general lighting applications. Available in a wide range of whites and multiple voltages.



Colour Temperature (K)

2700K 3000K 4000K 5000K 3500K		
Lens Options		
$\bigcirc \bigcirc \bigcirc$	$\bigcirc$	
Mounting Options		
Lumens	1200 lms/m (FS180)	
Electrical		
Input Voltage	12 VDC (FS180) 24 VDC (FS180)	
Power Consumption	14.4 W/m (FS180)	
Wire	Barrel, Locking Tab, Small Locking Tab, Blunt Wire	