





Experience the brilliance of Zortech LED's AL04 kit, featuring the FL60 (5050 SMD LED, 60 LED/m) strip and AL04 aluminum extrusion. Effortlessly combine LED illumination with the sleek AL04 square extrusion for a stunning lighting solution that adds both style and efficiency to any setting.

•Standard Semi-Clear (Frosted) Cover, other options available •Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request

·Variety of lead and wire options, at additional cost

Product Details	
Part Number	FL60, FL60 CC
Width	10mm wide, 5m spool
LED Count/m	60 LED/m (FL60, FL60 CC)
Cuttable Length	50mm (FL60, FL60 CC)
CRI	>80+ (FL60 CC) >90+ (FL60)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Powered by the standard 5050 standard SMD LED Chip, this flexible LED is great for general lighting applications. Available in a wide range of whites and multiple voltages.



Colour Temperature (K)

2200K 3000K 4000K 5000K 2700K 3500K 4500K		
Lens Options		
$\bigcirc \bigcirc$	\bigcirc	
Mounting Options		
Lumens	1000 lms/m (FL60) 1200 lms/m (FL60 CC)	
Electrical		
Input Voltage	12 VDC (Standard) 24 VDC (Standard, FL60 CC)	
Power Consumption	14.4 W/m (FL60) 12 W/m (FL60 CC)	
Wire	Barrel, Locking Tab, Small	

Locking Tab, Blunt Wire