

# 851106-FS180-VDC





Powered by the standard 2216 super small SMD LED Chip, this flexible LED is great for general lighting applications. Available in a wide range of whites and multiple voltages.



Experience the brilliance of Zortech LED's AL06 kit, featuring the FS180 (2216 SMD LED, 180 LED/m) strip and AL06 aluminum extrusion. Effortlessly combine high density LED illumination with the sleek ALO6 extrusion's sleek 45-degree design for a stunning lighting solution that adds both style and efficiency to any setting.

- ·Standard Semi-Clear (Frosted) Cover, other options available
- ·Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request
- ·Variety of lead and wire options, at additional cost

Colour Temperature (K)



## **Lens Options**







## **Mounting Options**









### **Product Details**

Part Number	FS180
Width	10mm wide, 5m spool
LED Count/m	180 LEDs/m (FS180)
Cuttable Length	17mm (FS180 12 VDC) 35mm (FS180 24 VDC)
CRI	>90+ (FS180)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Lumens 1200 lms/m (FS180)

#### **Electrical**

Input Voltage	12 VDC (FS180) 24 VDC (FS180)
Power Consumption	14.4 W/m (FS180)
Wire	Barrel, Locking Tab, Small Locking Tab, Blunt Wire