





Illuminate with Zortech LED's AL18 kit, featuring the HLFS64 (3528 SMD LED, 64 LED/m) strip and AL18 aluminum extrusion. Seamlessly merge high efficiency illumination with the AL18 extrusion's low ceiling design for a modern lighting solution that adds both style and practicality to any environment.

•Standard Semi-Clear (Frosted) Cover, other options available •Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request

 $\cdot Variety$ of lead and wire options, at additional cost

Product Details	
Part Number	HLFS64
Width	10mm wide, 5m spool (HLFS64)
LED Count/m	64 LED/m (HLFS64)
Cuttable Length	100mm (Standard)
CRI	>80+ (Standard)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Powered by the standard 3528 SMD LED Chip, this flexible LED is great for super bright lighting applications. Available in a wide range of whites and multiple voltages.



Colour Temperature (K)

▲ ▲ ▲ 2700K 3000K 4000K 5000K		
Lens Options		
$\bigcirc \bigcirc \bigcirc$	\bigcirc	
Mounting Options		
(1)		
Lumens	2100 lms/m (HLFS64)	
Electrical		
Input Voltage	24 VDC (Standard) Constant Current	
Power Consumption	11.4 W/m (HLFS64)	
Wire	Barrel, Locking Tab, Small Locking Tab, Blunt Wire	