

NEW

AL44 SERIES

851144-FL60-VDC



Powered by the standard 5050 standard SMD LED Chip, this flexible LED is great for general lighting applications. Available in a wide range of whites and multiple voltages.



Experience the brilliance of Zortech LED's AL44 kit, featuring the FL60 (5050 SMD LED, 60 LED/m) strip and AL44 aluminum extrusion. Effortlessly combine LED illumination with the sleek AL44 extrusion's domed design for a modern lighting solution that adds both style and efficiency to any setting.

- Standard Semi-Clear (Frosted) Cover, other options available
- Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request
- Variety of lead and wire options, at additional cost

Colour Temperature (K)



▲ ▲ ▲ ▲
2200K 3000K 4000K 5000K
2700K 3500K 4500K

Lens Options



Mounting Options



Product Details

| | |
|----------------|--|
| Part Number | FL60, FL60 CC |
| Width | 10mm wide, 5m spool |
| LED Count/m | 60 LED/m (FL60, FL60 CC) |
| Cutable Length | 50mm (FL60, FL60 CC) |
| CRI | >80+ (FL60 CC) >90+ (FL60) |
| IP Rating | IP20, IP65, IP67, IP68 |
| Lifespan | 50,000 hours (with recommended mounting to metal or glass surface) |

Lumens
1000 lms/m (FL60)
1200 lms/m (FL60 CC)

Electrical

Input Voltage
12 VDC (Standard)
24 VDC (Standard, FL60 CC)

Power Consumption
14.4 W/m (FL60)
12 W/m (FL60 CC)

Wire
Barrel, Locking Tab, Small Locking Tab, Blunt Wire

171



sales@zortechled.com / www.zortechled.com / +1 (905) 428-4298 / @ZortechLED
Zortech LED. All rights reserved.

Credit card payments subject to a 2.5% processing fee. Special/bulk orders may be subject to 50% deposit. Cheque or E-transfer to info@zortechled.com with invoice # please.