

NEW

# AL44 SERIES

## 851144-HLFS64-VDC



Powered by the standard 3528 SMD LED Chip, this flexible LED is great for super bright lighting applications. Available in a wide range of whites and multiple voltages.



Illuminate with Zortech LED's AL44 kit, featuring the HLFS64 (3528 SMD LED, 64 LED/m) strip and AL44 aluminum extrusion. Seamlessly merge high efficiency illumination with the AL44 extrusion's domed design for a modern lighting solution that adds both style and practicality to any environment.

- Standard Semi-Clear (Frosted) Cover, other options available
- Comes with 2 end caps and 2 mounting clips, other mounting options are available upon request
- Variety of lead and wire options, at additional cost

Colour Temperature (K)



▲ ▲ ▲ ▲  
2700K 3000K 4000K 5000K

### Lens Options



### Mounting Options



### Product Details

Part Number	HLFS64
Width	10mm wide, 5m spool (HLFS64)
LED Count/m	64 LED/m (HLFS64)
Cutable Length	100mm (Standard)
CRI	>80+ (Standard)
IP Rating	IP20, IP65, IP67, IP68
Lifespan	50,000 hours (with recommended mounting to metal or glass surface)

Lumens 2100 lms/m (HLFS64)

### Electrical

Input Voltage 24 VDC (Standard)  
Constant Current

Power Consumption 11.4 W/m (HLFS64)

Wire Barrel, Locking Tab, Small Locking Tab, Blunt Wire

