

Under Cabinet Fixture Kits

Specification Sheet

851025-X000K-X00-X

3000K

4000K

FS180-SMALL LED (3000K)

Wattage/m	Power	Lumens/m	Size	LED
10	12V DC	700	10mm wide	2216 LED
Ra	Rating	LEDS per meter	Increments	Dimmable
>80	IP20	180	100mm	Yes

Colour: 3000K (Warm White) Warranty: 3 years
 Lifespan: 50,000 hours (with recommended mounting to metal or glass surface)

FS180-SMALL LED (4000K)

Wattage/m	Power	Lumens/m	Size	LED
15	12V DC	1000	10mm wide	2216 LED
Ra	Rating	LEDS per meter	Increments	Dimmable
>80	IP20	180	100mm	Yes

Colour: 4000K (Natural White) Warranty: 3 years
 Lifespan: 50,000 hours (with recommended mounting to metal or glass surface)

12 VDC POWER SUPPLY

Wattage/m	Power	Voltage	Current	Rating
25	12V DC	100-240 VAC	2A	cETLus/Class II/FCC
Size		Connector		
80L x 41W x 38D mm		5.5/2.1 mm barrel connector		



These kits are perfect for standard sized cabinets and are available in warm white and neutral white, catering to different lighting preferences.

AL02 HOUSING

AL02 Aluminum Extrusion
 PC Opal Cover (Semi-Clear)
 Dimensions: 17.1mm x 8mm

POWER ENVIRONMENT

Indoor, on surface/Outdoor, covered

WORKING ENVIRONMENT

Temperature: -20°C to 40°C

